

# Band Saw K 220



The compact band saw K22 is ideal for cutting bones. The stainless steel housing is presented in an elegant design, secures high hygienically standards with its clogged working surface. The table top can be turned over and the doors can be opened wide for easy cleaning. The precise and narrow blade guide helps for a long lasting perfect cut. All movable parts can be easily cleaned as well as replaced. The saw convinces also through its safety: It contains a pusher for the material, safe coverings for the wheels and saw blade as well as a water safe electricity. The saw can also come with a fixed application and as an option with a frame construction. Long living bump rubbers care for a solid standing free of vibrations.

## **Technical Data:**

Wheel diameter:	220 mm
Band saw blade dimensions:	1820 x 16 mm
Tape speed:	16 m/sec.
Admission for the height of the cut:	230 mm
Admission for the breadth of the cut:	185 mm
Dimension of the cut:	215 mm
Table dimensions W/D/H:	405 x 555 x 385 mm
Total dimensions W/D/H:	515 x 595 x 930 mm
Engine output:	1,1 / IP 54
Engine speed:	1420 1/min
Voltage:	230 / 400 V
Nominal current:	4,7 / 2,7 V
Exhaust brake:	standard
Weight:	approx. 85 kg
Type:	K 220
Article No.:	020.020.010

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0  
Fax +49/941/20 86 48-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
*medical*  
■ ■ ■ ■

# Band Saw K 220



## **Blade guide**

The band saw is equipped with a precise and narrow guide for the saw blade which ensure a secure cutting.



## **Cleaning**

A perfect cleaning is ensured though the easy access by a wide opening of the doors and flipping up the table top.



## **Replacing the saw band**

The saw band can be easily changed using the quick-release artifice. To set the tape run the upper disc is setted over the star grip backsided. The convex contact surface of the rustproof discs guarantees a secure positioning of the saw band and the preservation of the offset.



## **Optional**

As an option we can offer you a frame construction suitable for the saw. The saw can be fixed with screws to this frame construction and is perfect for a working height of 920 mm.  
Article-No. 020.020.015

**KUGEL medical GmbH & Co. KG**  
Hermann-Köhl-Str. 2A  
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0  
Fax +49/941/20 86 48-29  
[www.KUGEL-medical.de](http://www.KUGEL-medical.de)



**KUGEL**  
*medical*